

ADVANTAGES



Economical



Light Weight



Abrasion Resistant



Fast and Reliable Jointing



Non Toxic



Recycled and Environment - Friendly

SOLID WALL CABLE PIPE

Outside Diameter (OD)	Wall Thickness (WT)		Standard Length
mm	Min (mm)	Max (mm)	Meter (m)
110	8.1	9.1	6m / 12m / 100m
160	11.8	13.1	6m / 12m
200	14.7	16.3	6m / 12m
250	18.4	20.4	6m / 12m

^{**} Dimension subject to manufacturing tolerances subject to changes without prior notice.

AZEETA PIPE SYSTEM SDN BHD (199701039760) (455260-W)

Sales Office:

No. 9, Jalan Anggerik Mokara 31/59, Kota Kemuning, 40460 Shah Alam, Selangor Darul Ehsan.

Lot 12694, Jalan TJ 2/3, Tuanku Ja'afar Industrial Park, Sungai Gadut, 71450 Seremban, Negeri Sembilan.

: +6 03 5121 8987 (Hunting Line),

+6 03 5121 8845 +6 03 5121 7846

Fax : +6 03 5121 8978

Email: wktneh@azeetapipe.com

azeetaivin@gmail.com

^{**} Other manufacturing dimension is acceptable upon request.